FOLDER-GLUERS COLT AUTOMATIC BOX PACKER



HIGH RESPONSIVE CARTON CONVERTING MACHINERY









Boosting productivity solution

BUNDLING & STRAPPING

Introducing the Colt, a fully automatic bundling and strapping machine designed for medium to large packaging needs. It handles a wide variety of box types, from straight line and crash-lock bottom to 4- and 6-corner, accommodating materials like cardboard, micro-flute, and corrugated up to 5 layers.

With advanced features such as counting, 180° turning, stacking, strapping, and bundling, the Colt integrates seamlessly with all folder gluers on the market, boosting productivity and reducing labor costs in one streamlined pass.

AT A GLANCE



FAST PROCESSING



WIDE RANGE



MATERIALS

Cardborad Micro-flute Corrugated




FLEXIBLE & EASY TO OPERATE





CERTIFICATED

BOXES



Straight line




Double - wall




Lock - bottom



4 - corner



4 - corner with Lid



6 - corner









The Delivery Section smoothly transports the finished package, making it easy to collect and prepare for delivery.



Final bundling & strapping of the box batch, creating a tight, square package that is easy to handle, deliver, and palletize.



Ensures that boxes oriented in both directions are aligned and squared perfectly.



Rotates every other group of boxes 180°, ensuring that the batch is evenly squared and properly oriented.



Accurately counts boxes and separates them into groups of specific units, ensuring precise organization for the next step.


ADGM


SPECIFICATIONS

COLT	
Processed materials	
Carton board max.	1200 g/m ²
Corrugated flute type	B, C, N, E, F, AB, 3 & 5 layers
Capability	
Speed max.	9 s/bundle (full configuration)
	4.5 s/bundle (counting & separation, stacking)
Bundle height	80 - 300 mm
Folded box width	235 - 800 mm
Folded box length	230 - 800 mm
Distance between strap edge to box edge	Min. 80 mm
Distance between straps	Min. 170 mm
Bundle	Min. W100 x L120 x H30 mm
	Max. W400 x L430 x H140 mm
Strap type	PP, PE
Dimensions & weight	
Length	7.6 m (full configuration)
	4.3 m (counting & separation, stacking)
Width	1.9 m
Height	2.13 m (full configuration)
	1.8 m (counting & separation, stacking)
Weight	9000 kg (full configuration)
	3500 kg (counting & separation, stacking)
Installation	
Power supply	25 kw (full configuration)
	10 kw (counting & separation, stacking)
Compressed air	6 bar
Air compressor capacity	30 m3/h
Air tank capacity	155 L



SCHEME COLT







info@dgm-global.com www.dgm-global.com

TEL (86) 0752-277 37 80 FAX (86) 0752-277 37 78

HuiHuan Industrial Area, Huizhou City, Guangdong Province, China

DGM Technology (China) Co., Ltd